

Page: 1 of 9

Revised edition no: 3

Date: 1/6/2014

Supersedes: 1 / 11 / 2012

Nitrogen (refrigerated)

EIGA089B



Warning



SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Nitrogen (refrigerated)

SDS no : EIGA089B

Chemical description : Nitrogen (refrigerated)

CAS No :7727-37-9 EC No :231-783-9 Index No :---

Registration-No. : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : N2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional. Perform risk assessment prior to use.

Use for manufacture of electronic/photovoltaic components.

Test gas/Calibration gas. Purging. Laboratory use.

Shield gas for welding processes.

Purge gas, diluting gas, inerting gas.

Contact supplier for more information on uses.

1.3. Details of the supplier of the safety data sheet

Company identification : THE NETHERLANDS:

AIR LIQUIDE BV De Witbogt 1 5652 AG Eindhoven the Netherlands-Nederland

BELGIUM:

AIR LIQUIDE BELGE S.A./N.V.

Quai des Vennes, 8 B-4020 Liège-Luik Belgium-Belgique-België

LUXEMBURG:

L'AIR LIQUIDE LUXEMBOURG S.A.

ZONE P.E.D.-B.P.20

L-4801 RODANGE Luxemburg

1.4. Emergency telephone number

Emergency telephone number : THE NETHERLANDS: +31 (0)40 250 35 03

BELGIUM: +32 (0)4 349 89 89 LUXEMBURG: +352 50 62 63 1

National Poisons Information Centre the Netherlands: 030-2748888

Poison centre Belgium: 070 245 245

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 2 of 9

Revised edition no: 3

Date: 1 / 6 / 2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Hazard Class and Category Code Regulation EC 1272/2008 (CLP)

• Physical hazards : Gases under pressure - Refrigerated liquefied gas - Warning - (CLP: Press. Gas Ref. Liq.) -

H28⁻

Classification EC 67/548 or EC 1999/45

: Not classified as dangerous substance / mixture.

Not included in Annex VI. No EC labelling required.

2.2. Label elements

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



• Hazard pictograms code : GHS04 • Signal word : Warning

• Hazard statements : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

• Precautionary statements

- **Prevention** : P282 - Wear cold insulating gloves/face shield/eye protection.

- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get

immediate medical advice / attention.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

: Asphyxiant in high concentrations.

SECTION 3. Composition/information on ingredients

3.1. Substance / 3.2. Mixture

Substance.

Substance name		Contents	CAS No EC No Index No Registration No	Classification(DSD)	Classification(CLP)
Nitrogen (refrigerated)	:	100 %	7727-37-9 231-783-9	Not classified (DSD)	Press. Gas Ref. Liq. (H281)
			 * 1		

Contains no other components or impurities which will influence the classification of the product.

* 1: Listed in Annex IV / V REACH, exempted from registration.

* 2: Registration deadline not expired.

* 3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of R-phrases see section 16. Full text of H-statements see section 16.

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 3 of 9

Revised edition no: 3

Date: 1 / 6 / 2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 4. First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5. Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None

5.3. Advice for fire fighters

Specific methods : Move containers away from the fire area if this can be done without risk.

Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

If possible, stop flow of product.

If leaking do not spray water onto container. Water surrounding area (from protected position)

to contain fire.

Use water spray or fog to knock down fire fumes if possible.

Special protective equipment for fire

fighters

Use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for

firefighters

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Try to stop release.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to

be safe.

Evacuate area. Use protective clothing.

Ensure adequate air ventilation.

Prevent from entering sewers, basements and workpits, or any place where its accumulation

can be dangerous.

Act in accordance with local emergency plan.

Stay upwind.

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 4 of 9

Revised edition no: 3

Date: 1/6/2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 6. Accidental release measures (continued)

6.2. Environmental precautions

: Try to stop release.

6.3. Methods and material for containment and cleaning up

Liquid spillages can cause embrittlement of structural materials.
 Ventilate area.

6.4. Reference to other sections

: See also sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Only experienced and properly instructed persons should handle gases under pressure. The substance must be handled in accordance with good industrial hygiene and safety procedures.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Consider pressure relief device(s) in gas installations.

Do not breathe gas.

Avoid release of product into atmosphere.

Safe handling of the gas receptacle

Refer to supplier's container handling instructions.

Suck back of water into the container must be prevented.

Do not allow backfeed into the container.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container.

7.2. Conditions for safe storage, including any incompatibilities

: Observe all regulations and local requirements regarding storage of containers. Keep container below 50°C in a well ventilated place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition.

Containers should not be stored in conditions likely to encourage corrosion. Keep away from

combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

DNEL: Derived no effect level (

Workers)

: No data available.

PNEC: Predicted no effect

concentration

: No data available.

8.2. Exposure controls

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 5 of 9 Revised edition no: 3 Date: 1/6/2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 8. Exposure controls/personal protection (continued)

8.2.1. Appropriate engineering

controls

Systems under pressure should be regularily checked for leakages.

Oxygen detectors should be used when asphyxiating gases may be released.

Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.

e.g. personal protective equipment

8.2.2. Individual protection measures, : PPE compliant to the recommended EN/ISO standards should be selected.

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered: Protect eyes, face and skin from liquid splashes.

Wear goggles and a face shield when transfilling or breaking transfer connections. · Eye/face protection

Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection.

Skin protection

: Wear working gloves when handling gas containers. - Hand protection

Standard EN 388 - Protective gloves against mechanical risk.

- Other : Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

· Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

 Thermal hazards Standard EN 511 - Cold insulating gloves.

Wear cold insulating gloves when transfilling or breaking transfer connections.

8.2.3. Environmental exposure

controls

: None necessary.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas.

Colour : Colourless liquid.

Odour : No odour warning properties.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH value : Not applicable.

Molar mass [g/mol] : 28 Melting point [°C] : -210 : -196 Boiling point [°C] Critical temperature [°C] : -147

: Not applicable for gases and gas mixtures. Flash point [°C] : Not applicable for gases and gas mixtures. Evaporation rate (ether=1)

: Non flammable.

Vapour pressure [20°C] : Not applicable. Relative density, gas (air=1) : 0.97 Relative density, liquid (water=1) : 0.8

Solubility in water [mg/l] : 20

Partition coefficient n-octanol/water [: Not applicable for inorganic gases.

Flammability range [vol% in air]

log Kow]

Auto-ignition temperature [°C] : Not applicable. Viscosity at 20°C [mPa.s] : Not applicable. : Not applicable. **Explosive Properties** · None **Oxidising Properties**

9.2. Other information

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 6 of 9 Revised edition no: 3 Date: 1/6/2014 Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 9. Physical and chemical properties (continued)

Other data Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

SECTION 10. Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

: Stable under normal conditions.

10.3. Possibility of hazardous reactions

· None

10.4. Conditions to avoid

: None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

: None.

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

: None

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity : No known toxicological effects from this product.

: No known effects from this product. Skin corrosion/irritation : No known effects from this product. Serious eye damage/irritation Respiratory or skin sensitisation : No known effects from this product. Carcinogenicity : No known effects from this product. Germ cell mutagenicity : No known effects from this product. Reproductive toxicity : No known effects from this product. STOT-single exposure : No known effects from this product. STOT-repeated exposure : No known effects from this product. **Aspiration hazard** : Not applicable for gases and gas mixtures.

SECTION 12. Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB.

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 7 of 9

Revised edition no: 3

Date: 1/6/2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 12. Ecological information (continued)

12.6. Other adverse effects

: Can cause frost damage to vegetation.

Effect on the ozone layer : None.
Effect on global warming : None.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

: May be vented to atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Refer to the EIGA code of practice Doc.30 ""Disposal of Gases"", downloadable at http://www.

eiga.org for more guidance on suitable disposal methods. Consult supplier for specific recommendations.

List of hazardous waste codes (from Commission Decision 2001/118/EC)

: 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

: None.

SECTION 14. Transport information

14.1. UN number

UN number : 1977

Labelling ADR, IMDG, IATA



: 2.2 : Non-flammable, non-toxic gases

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : NITROGEN, REFRIGERATED LIQUID
Transport by air (ICAO-TI / IATA-DGR) : NITROGEN, REFRIGERATED LIQUID
Transport by sea (IMDG) : NITROGEN, REFRIGERATED LIQUID

14.3. Transport hazard class(es)

Transport by road/rail (ADR/RID)

Class : 2 Classification code : 3 A H.I. nr : 22

Tunnel Restriction : C/E Tank carriage: Passage forbidden through tunnels of category C, D and E; Other carriage:

Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Division (Subsidiary risk(s)) : 2.2

Transport by sea (IMDG)

Class / Division (Subsidiary risk(s)) : 2.2 Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable.

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 8 of 9 Revised edition no: 3 Date: 1/6/2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 14. Transport information (continued)

Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None. Transport by air (ICAO-TI / IATA-DGR) : None. Transport by sea (IMDG) : None.

14.6 Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Allowed. Packing instruction - Passenger and : 202

Cargo Aircraft

Cargo Aircraft only : Allowed. Packing instruction - Cargo Aircraft : 202

: P203 Transport by sea (IMDG)

: Avoid transport on vehicles where the load space is not separated from the driver's Special precautions for user

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency. Before transporting product containers: - Ensure that containers are firmly secured.

- Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

- Ensure there is adequate ventilation.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk according to Annex : Not applicable. II of MARPOL 73/78 and the IBC Code

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions on use : None. Seveso directive 96/82/EC : Not covered.

National legislation

National legislation : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1



Page: 9 of 9

Revised edition no: 3

Date: 1/6/2014

Supersedes: 1 / 11 / 2012

EIGA089B

Nitrogen (refrigerated)

SECTION 16. Other information

Indication of changes
Training advice
Further information

- : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
- : The hazard of asphyxiation is often overlooked and must be stressed during operator training.
- This Safety Data Sheet has been established in accordance with the applicable European Union legislation.

List of full text of H-statements in section 3.

: H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

section 3.
DISCLAIMER OF LIABILITY

: Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

The contents and format of this SDS are in accordance with EC Commission Directive 2001/58/EC.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document

AIR LIQUIDE In case of emergency: NL: +31 (0) 40 250 35 03 / BE: +32 (0)4 349 89 89 / LUX: +352 50 62 63 1